

Cable Configurator - Requirements



PERSONAL DATA:

Name:

Company:

Address:

Phone:

E-mail:

General information	norm	<input type="checkbox"/> factory standard	<input type="checkbox"/> DIN	<input type="checkbox"/> other norm					
	demand m	<input type="checkbox"/> per month	<input type="checkbox"/> once	<input type="checkbox"/> continuously				
			<input type="checkbox"/> per year	<input type="checkbox"/> sporadically	<input type="checkbox"/> sample				
	conditions of use	<input type="checkbox"/> outside	<input type="checkbox"/> inside	<input type="checkbox"/> other:					
		<input type="checkbox"/> permanent	<input type="checkbox"/> mobile	<input type="checkbox"/> highly flexible	<input type="checkbox"/> other:				
	operational voltage: V Hz						
	test voltage (eff.)	core/core: V	min core/screen	V	min screen/ screen:			
	direct current resistance	core:	Ω/km	screen:	Ω/km	loop:			
	capacity	core/screen:	pF/m	core/core:	pF/m	other:			
	charact. impedance: Ω	attenuation:	dB/100 m at	MHz				
				dB/100 m at	MHz			
	Conductor	exact purpose of use:							
tempera- ture:		environ- ment:	°C	temperature stress:	duration:	°C	min short-time:	°C	min
chem. use:		other impact:							
		<input type="checkbox"/> copper	<input type="checkbox"/> CCS	<input type="checkbox"/> other:	<input type="checkbox"/> wire: ∅	mm	<input type="checkbox"/> strand: ∅	mm	
Insulation	cross section: mm ²	number of wires:	x	x ∅	mm			
		<input type="checkbox"/> bare	<input type="checkbox"/> tin-plated	<input type="checkbox"/> silver-plated	<input type="checkbox"/> nickel-plated	<input type="checkbox"/> other		
		<input type="checkbox"/> PE	<input type="checkbox"/> Cell-Pe	<input type="checkbox"/> PVC	<input type="checkbox"/> Teflon	<input type="checkbox"/> PA	<input type="checkbox"/> PUR	<input type="checkbox"/> cavity	<input type="checkbox"/> other
Coaxial cable	thickness:mm	core labeling:	<input type="checkbox"/> with numbers				
		<input type="checkbox"/> colored	<input type="checkbox"/> acc. to code/norm	<input type="checkbox"/> other			
	<input type="checkbox"/> Coaxial cable								
	semiconducting layer:	∅	mm	<input type="checkbox"/> PE	<input type="checkbox"/> PVC	<input type="checkbox"/> other		
Screen	<input type="checkbox"/> Cu foil	<input type="checkbox"/> Al foil	<input type="checkbox"/> Cu band	<input type="checkbox"/> braid	<input type="checkbox"/> wrap	<input type="checkbox"/> bare	<input type="checkbox"/> tinned	<input type="checkbox"/> silver-plated	
	construc- tion:	∅	mm	lay length:	mm	opt. coverage:	%	<input type="checkbox"/> other	
	filler wire:	∅	mm		<input type="checkbox"/> bare	<input type="checkbox"/> tinned	<input type="checkbox"/> silver-plated		
Jacket	<input type="checkbox"/> PE	<input type="checkbox"/> PVC	<input type="checkbox"/> Teflon	<input type="checkbox"/> PA	<input type="checkbox"/> PUR	<input type="checkbox"/> foil	<input type="checkbox"/> other	
	thickness:	mm	max. outer ∅:	mm	color:	

Cable configurator - Requirements



Control cable	<input type="checkbox"/> Control cable						
	number/ cores:	x.....mm ²	number/ cores:	x.....mm ²	number/ cores:	x.....mm ²	
	number other:	type:	construction:				
	<input type="checkbox"/> stranding	<input type="checkbox"/> foil	<input type="checkbox"/> individual shielding	<input type="checkbox"/> overall shielding	<input type="checkbox"/> jacket		
Combined cable	<input type="checkbox"/> Combined cable						
	Number of coax cables:	type:	construction:				
	number/ cores:	x.....mm ²	number/ cores:	x.....mm ²	number/ cores:	x.....mm ²	
	number other:	type:	construction:				
<input type="checkbox"/> stranding	<input type="checkbox"/> foil	<input type="checkbox"/> individual shielding	<input type="checkbox"/> overall shielding	<input type="checkbox"/> jacket			
Shielding	<input type="checkbox"/> Cu foil <input type="checkbox"/> Al foil <input type="checkbox"/> Cu band <input type="checkbox"/> braid <input type="checkbox"/> wrap <input type="checkbox"/> bare <input type="checkbox"/> tinned <input type="checkbox"/> silver-plated						
	construction:	∅	mm	lay length:	mm	opt. cover- age:	% <input type="checkbox"/> other:
	filler wire:	∅	mm	<input type="checkbox"/> bare	<input type="checkbox"/> tinned	<input type="checkbox"/> silver-plated	
Jacket	<input type="checkbox"/> PE <input type="checkbox"/> PVC <input type="checkbox"/> teflon <input type="checkbox"/> PA <input type="checkbox"/> PUR <input type="checkbox"/> other:						
	thickness:	mm	max. outer ∅:	mm	color:		
	<input type="checkbox"/> labeling	<input type="checkbox"/> embossing	<input type="checkbox"/> imprint	text:			
Armouring	<input type="checkbox"/> band <input type="checkbox"/> double- layer band <input type="checkbox"/> round wire <input type="checkbox"/> torsion-free counter- rotating round wire <input type="checkbox"/> flat wire						
	<input type="checkbox"/> braided steel wire <input type="checkbox"/> other:						
	number of wires:	x	x ∅.....mm	<input type="checkbox"/> galvanized	<input type="checkbox"/> non corrosive	<input type="checkbox"/> other:	strength:
Jacket	<input type="checkbox"/> PE <input type="checkbox"/> PVC <input type="checkbox"/> teflon <input type="checkbox"/> PA <input type="checkbox"/> PUR <input type="checkbox"/> other:						
	thickness:	mm	max. outer ∅:	mm	color:		
	<input type="checkbox"/> labeling	<input type="checkbox"/> embossing	<input type="checkbox"/> imprint	text:			
Support	<input type="checkbox"/> steel wire ∅:						
	mm	<input type="checkbox"/> steel rope	∅:	mm	<input type="checkbox"/> Kevlar®	∅:	mm <input type="checkbox"/> other:
Attach- ments	<input type="checkbox"/> specification <input type="checkbox"/> sample <input type="checkbox"/> other:						

Further Information:

bda connectivity GmbH
Herborner Str. 61 a
35614 Asslar
Germany

Phone: +49 6441 38452 0
Fax: +49 6441 38452 99
E-mail: info@bda-c.com
www.bda-connectivity.com